

Vista

Vista 200, Vista 100
P 13 BTE hearing aid



P 13


Performance profile	Vista 200	Vista 100
Channels / bands	3/6	2/4
Processing types	WDRC and linear	WDRC and linear
Fixed directional	•	
Omni directional		•

Signature features		
AutoMic	•	

Features		
Manual programs	Up to 3	Up to 2
Automatic Adaptation Manager	•	•
Noise reduction	1 setting	1 setting
Speech intensifier	1 setting	1 setting
Feedback manager	•	•
Natural Sound	•	•
Pulse protector	1 setting	1 setting
Wind noise manager	1 setting	1 setting
MyMusic	•	•
Telecoil	•	
DAI	•	
Data logging	•	•
IntelliVent technology for custom ear pieces	•	•
Optional EasyFit system for instant fitting	•	•
Plasma coating	•	•
IP57	•	•

Class	P 13
Peak output / gain 2cc unfiltered earhook	133 / 63
Peak output / gain slim tube	121 / 54
Battery size	13






Fitting guides







Vista P 13 BTE series

Filtered earhook (standard) Unfiltered earhook (optional) Slim tube (optional)

ANSI 3.22 2009/IEC 118-7 2005 2cc coupler technical data

	Reference test frequency - IEC 118-7 (kHz)	1.6	1.6	1.6
	OSPL90			
	Maximum (dB SPL)	128	133	121
	Nominal (dB SPL)	125	130	118
	HFA - OSPL90 (dB SPL)	122	123	107
	at RTF (dB SPL)	118	118	104
	Full on gain (input 50 dB SPL)			
	Maximum (dB)	58	63	54
	HFA - FOG (dB)	54	56	39
	at RTF (dB)	50	50	36
	Reference test setting (RTS)			
	Frequency range (Hz)	100-6000	100-6000	100-6000
	Reference test gain (dB)	45	46	30
	Current drain at RTS (mA)	1.1	1.1	1.1
	Typical battery life (h)	282	282	282
	Equivalent input noise at RTS (dB SPL)	19	19	19
	Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)	2.5/2/1	2.5/2/1	2.5/2/1
	Induction coil sensitivity (31.6 mA/m)			
	HFA SPLITS/STS-RSETS (dBSPL/dB)	103/-1	107/-1	88/1
	Standard: mic at 70 dB SPL vs induction coil at 100 mA/m			
	— Mic			
	- - Induction coil			
	Electromagnetic compatibility			
	EMC immunity by ANSI c63.19-2001 EMC, omni/telecoil	M2/T2	M2/T2	M2/T2

IEC 118-o OES coupler technical data

	Reference test frequency - IEC 118-o (kHz)	1.6	1.6	1.6
	OSPL90			
	Maximum (dB SPL)	133	134	124
	at RTF (dB SPL)	126	127	113
	Full on gain (input 50 dB SPL)			
	Maximum (dB)	66	68	59
	at RTF (dB)	59	60	46
	Basic frequency response			
	Frequency range (DIN 45605) (Hz)	100-6900	100-6900	100-6900
	Reference test gain (dB)	51	52	38
	Current drain at RTG (mA)	1.1	1.1	1.1
	Typical battery life (h)	282	282	282
	Equivalent input noise at RTG (dB SPL)	19	19	19
	Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)	2.5/2/1	2.5/2/1	2.5/2/1
	Induction coil sensitivity			
	at RTF (graph shown for 31.6 mA/m at RTG) (dB SPL)	111	111	98
	Maximum (1 mA/m at full on gain) (dB SPL)	95	95	87
	at RTF (1 mA/m at full on gain) (dB SPL)	88	85	75
	Electromagnetic compatibility			
	EMC immunity by IEC 60118-13, 2011 field strength 90/50/35 V/m, omni IRIL low/medium/high band (dB SPL)	33/53/52	33/53/52	33/53/52

Legend

- Unfiltered earhook
- Filtered earhook

Test conditions

Battery size: 13; Source: voltage 1.3 V; Tubing: length 25 mm, inside diameter 1.93 mm
Hearing instrument set to Vista:fit test settings.

Domes should never be fit on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend use of a customized earmold.

Sound pressure level of these hearing aids exceeds 132 dB SPL.

We reserve the right to change specification data without notice as improvements are introduced.