

Vista


Vista 300 ITE hearing aid series




Performance profile	Vista 300
Channels / bands	4/8
Processing types	WDRC and linear
Adaptive directional	•
Fixed directional	•
Signature features	
AutoMic	•
Features	
Manual programs	Up to 4
Automatic Adaptation Manager	•
Noise reduction	3 settings
Speech intensifier	3 settings
Feedback manager	•
Natural Sound	•
Pulse protector	3 settings
Wind noise manager	3 settings
MyMusic	•
Telecoil	•
Data logging	•
IntelliVent technology	•

Battery size	Full shell	Half shell	Canal	Mini canal	CIC	Microphone
13	Standard	Optional	Optional	N/A	N/A	Directional
312	Optional	Standard	Standard	N/A	N/A	Directional
10A	Optional	Optional	Optional	Standard	Standard	Omni


Fitting guides




Moderate power



Power



High power



Super power (13 & 312 only)

Vista 300 ITE series

Moderate power Power High power Super power

ANSI 3.22 2009/IEC 118-7 2005 2cc coupler technical data

	Reference test frequency - IEC 118-7 (kHz)	1.6	1.6	1.6	1.6
	OSPL90				
	Maximum (dB SPL)	112	118	122	130
	Nominal (dB SPL)	109	115	119	127
	HFA - OSPL90 (dB SPL) at RTF (dB SPL)	103	111	114	120
	Full on gain (input 50 dB SPL)				
	Maximum (dB)	40	50	60	70
	HFA - FOG (dB)	37	46	54	62
	at RTF (dB)	35	43	53	70
	Reference test setting (RTS)				
	Frequency range (Hz)	100-7500	100-7500	100-7100	100-5500
	Reference test gain (dB)	26	34	37	43
	Current drain at RTS (mA) 10A/312/13	1.2/1.2/1.2	1.4/1.4/1.4	1.2/1.2/1.2	--/1.2/1.2
	Typical battery life (h) 10A/312/13	80/150/260	70/130/220	80/150/260	--/150/260
	Equivalent input noise at RTS (dB SPL)	19	19	19	19
	Induction coil sensitivity (31.6 mA/m)				
	HFA SPLITS/STS (dB SPL/dB)	88/2	95/1	99/2	104/1
	Electromagnetic compatibility EMC immunity by ANSI C63.19-2001 EMC, omni/telecoil M4/T4 M4/T4 M4/T4 M4/T4				

IEC 118-o OES coupler technical data

	Reference test frequency - IEC 118-o (kHz)	1.6	1.6	1.6	1.6
	OSPL90				
	Maximum (dB SPL)	120	124	128	133
	at RTF (dB SPL)	111	119	121	132
	Full on gain (input 50 dB SPL)				
	Maximum (dB)	50	60	70	79
	at RTF (dB)	44	53	62	76
	Basic frequency response				
	Frequency range (DIN 45605) (Hz)	100-8200	100-8200	100-7500	100-5500
	Reference test gain (dB)	36	44	46	57
	Current drain at RTG (mA) 10A/312/13	1.2/1.2/1.2	1.2/1.2/1.2	1.2/1.2/1.2	--/1.2/1.2
	Typical battery life (h) 10A/312/13	80/150/260	80/150/260	80/150/260	--/150/260
	Equivalent input noise at RTG (dB SPL)	19	19	19	19
	Induction coil sensitivity				
	at RTF (graph shown for 31.6 mA/m at RTG) (dB SPL)	96	104	106	119
	Maximum (1 mA/m at full on gain) (dB SPL)	83	92	102	110
	at RTF (1 mA/m at full on gain) (dB SPL)	76	85	94	108
Electromagnetic compatibility EMC immunity by IEC 60118-13, 2011 field strength 90/50/35 V/m, omni, IRIL low/medium/high band (dB SPL) 26/30/35 26/30/35 26/30/35 26/30/35					

Legend

- Super power
- High power
- Power
- Moderate power

Test conditions

Battery size: 10A/312/13; Source voltage: 1.3 V; Vent: closed at canal end
 Tubing 7mm (2cc/OES coupler) – Vista 300 M, Vista 300 P, Vista 300 HP.
 Tubing 9 mm (2cc coupler), Tubing 5mm (OES coupler) – Vista 300 SP.
 The hearing instrument set to Vista:fit test settings.
 Sound pressure level of these hearing aids exceeds 132 dB SPL.
 We reserve the right to change specification data without notice as improvements are introduced.